

STATE OF OREGON DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES www.OregonGeology.org Larry Givens, Governing Board Chair Vicki S. McConnell, Director and State Geologist Andree V. Pollock, Assistant Director Geologic Survey and Services Rachel R. Lyles Smith, Project Operations Manager Ian P. Madin, Chief Scientist

Map Explanation

the map area.

This tsunami inundation map displays the output of computer models

representing the two selected tsunami scenarios: Alaska M9.2 (1964)

and the Alaska Maximum. All tsunami simulations were run assuming

the higher high tides observed over an 18-year period at the Port Orford tide gauge. The map legend depicts the respective amounts of

deformation and the earthquake magnitude for these two scenarios.

Figure 3 shows the cumulative number of buildings inundated within

The computer simulation model output is provided to DOGAMI as

millions of points with values that indicate whether the location of each point is wet or dry. These points are converted to wet and dry

contour lines that form the extent of inundation. The transition area

between the wet and dry contour lines is termed the Wet/Dry Zone, which equates to the amount of error in the model when determining

the maximum inundation for each scenario. Only the Alaska

This map also shows the regulatory tsunami inundation line (Oregon

Revised Statutes 455.446 and 455.447), commonly known as the

Senate Bill 379 line. Senate Bill 379 (1995) instructed DOGAMI to establish the area of expected tsunami inundation based on scientific

evidence and tsunami modeling in order to prohibit the construction

of new essential and special occupancy structures in this tsunami

Time Series Graphs and Wave Elevation Profiles. In addition to the tsunami scenarios, the computer model produces time series data for

"gauge" locations in the area. These points are simulated gauge

stations that record the time, in seconds, of the tsunami wave arrival and the wave height observed. It is especially noteworthy that the

greatest wave height and velocity observed are not necessarily

associated with the first tsunami wave to arrive onshore. Therefore

evacuees should not assume that the tsunami event is over until the

proper authorities have sounded the all-clear at the end of the

evacuation. Figure 4 depicts the tsunami waves as they arrive at a simulated gauge station. Figure 5 depicts the overall wave height and

inundation extent for the two scenarios at the profile locations shown

subduction can trigger tsunamis.

Maximum Wet/Dry Zone is shown on this map.

inundation zone (Priest, 1995).

on this map.

that prevailing tide was static (no flow) and equal to Mean Higher High Water (MHHW) tide; MHHW is defined as the average height of

## Introduction

The Oregon Department of Geology and Mineral Industries (DOGAMI) has been identifying and mapping the tsunami inundation hazard along the Oregon coast since 1994. In Oregon, DOGAMI manages the National Tsunami Hazard Mitigation Program, which has been administered by the National Oceanic and Atmospheric Administration (NOAA) since 1995. DOGAMI's work is designed to help cities, counties, and other sites in coastal areas reduce the potential for disastrous tsunami-related consequences by understanding and mitigating this geologic hazard. Using federal funding awarded by NOAA, DOGAMI has developed a new generation of tsunami inundation maps to help residents and visitors along the entire Oregon coast prepare for the next Cascadia Subduction Zone (CSZ) earthquake and tsunami, as well as for far-travelled, or "distant" tsunamis.

The "Ring of Fire", also called the Circum-Pacific belt, is the zone of earthquake activity surrounding the Pacific Ocean. It is an arc stretching from New Zealand, along the eastern edge of Asia, north across the Aleutian Islands of Alaska, and south along the coast of North and South America (Figure 1). The Ring of Fire is located at the borders of the Pacific Plate and other major tectonic plates. The Pacific Plate is colliding with and sliding underneath other plates creating subduction zones that eventually release energy in the form of an earthquake rupture. This rupture causes a vertical displacement of water that creates a tsunami. When these events occur around the Ring of Fire but not directly off the Oregon coast, they take more time to travel the Pacific Ocean and arrive onshore in Oregon (Figure 2). Distant earthquake/tsunami events have affected the Oregon coast: for example, offshore Alaska in 1964 and offshore Japan in March 2011.

Historically, about 28 distant tsunamis have been documented by Oregon tide gauges since 1854. The most severe was generated by the 1964 M9.2 Prince William Sound earthquake in Alaska. Oregon was hit hard by the tsunami, which killed four people and caused an estimated 750,000 to 1 million dollars in damage to bridges, houses, cars, boats, and sea walls. The greatest tsunami damage in Oregon did not occur along the ocean front as one might expect, but in the estuary channels located further inland. Of the communities affected, Seaside was inundated by a 10 foot tsunami wave and was the hardest hit. Tsunami wave heights reached 10 to 11.5 feet in the Nehalem River, 10 to 11.5 feet at Depoe Bay, 11.5 feet at Newport, 10 to 11 feet at Florence, 11 feet at Reedsport, 11 feet at Brookings, and 14 feet at Coos Bay (Witter and others, 2011).

Alaska-Aleutian Model Specifications. DOGAMI modeled two distant earthquake and tsunami scenarios involving M9.2 earthquakes originating near the Gulf of Alaska. The first scenario attempts to replicate the 1964 Prince William Sound event, and the second scenario represents a hypothetical maximum event. This maximum event is the same model used by the U.S. Geological Survey (USGS) in their 2006 tsunami hazard assessment of Seaside (TPSW, 2006). This model uses extreme fault model parameters that result in maximum seafloor uplift, nearly twice as large as in the 1964 earthquake. The selected source location on the Aleutian chain of islands also shows higher energy directed toward the Oregon coast than other Alaskan source locations. For these reasons the hypothetical "Alaska Maximum" scenario is selected as the worst case distant tsunami scenario for Oregon. Detailed information on fault geometries, subsidence, computer models, and the methodology used to create the tsunami scenarios presented on this map can be found in DOGAMI Special Paper 43 (Witter and others, 2011).

### Ring of Fire



Prince William Sound 1964 M9.2 Earthquake and Tsunami Travel Time Map



## Buildings within Tsunami Inundation Zones



Figure 4: This chart depicts the tsunami waves as they arrive at the selected reference point (simulated gauge station). It shows the change in wave heights for the two Alaska tsunami scenarios over an 8-hour period. Wave heights vary through time, and the first wave will not necessarily be the largest as waves interfere and reflect off local topography and bathymetry.

# Distant Source (Alaska-Aleutian Subduction Zone) Tsunami Inundation Map Langlois, Oregon



Estimated Tsunami Wave Height through Time for Simulated Gauge Station

No Gauge Station For Map Extent

Maximum Wave Elevation Profiles



Figure 5: These profiles depict the expected maximum tsunami wave elevation for the two Alaska tsunami scenarios along lines A-A' and B-B'. The tsunami scenarios are modeled to occur at static (no flow) tide and equal to the Mean Higher High Water (MHHW) high tide.

Tsunami Inundation Map Index 01 02 03 06 BAI 07 08 `\_\_ OREGON໌ 11 6 14 15 Curr-09 Gold Beach Curr-01 Langlois Curr-02 Cape Blanco Curr-10 Cape Sebastian Curr-03 Denmark Curr-11 Pistol River Curr-04 Port Orford Curr-12 Carpenterville Curr-05 Humbug Mountain Curr-13 Harris Beach Curr-06 Sisters Rock Curr-14 Chetco River Curr-15 Winchuck River Curr-07 Nesika Beach Curr-08 North Rogue River Curr-16 Brookings



Tsunami Inundation Map Curr-01 Tsunami Inundation Maps for Langlois, Curry County, Oregon Plate 2

## Legend

arthquake Size		Slip / Deformation			Magnitude
	Alaska M9.2 (1964)	Vertical seafloor deformation estimate.		ation	~9.2
	Alaska Maximum	Uniform slip on 12 subfaults with each assigned values ranging from 49 to 98 feet.		aults with nging	~9.2
	Alaska Maximum Wet/	'Dry Zone			
	Urban Growth Bounda	ary	•	Fire Statior	ı
	Building Footprint		٠	Police Stati	on
6	Simulated Gauge Stati	on	•	School	
	Profile Location		•	Hospital/U	rgent Care Clinic
	Senate Bill 379 Line			U.S. Highwa	ау
	State Park		<b>—</b> 241) <b>—</b>	State High	мау
Ø	Elevation Contour (25 ft intervals up to 2	200 ft)		Improved F	Road

## Data References

Earthquake

1 Kilometer

Source Data: This map is based on hydrodynamic tsunami modeling by National Geophysical Data Center / World Data Center Joseph Zhang, Oregon Health and Science University, Portland, Oregon. Model data input were created by John T. English and George R. Priest, Department of Geology and Mineral Industries (DOGAMI), Portland, Oregon. Hydrology data, contours, critical facilities, and building footprints were created by DOGAMI. Senate Bill 379 line data were redigitized by Rachel R. Lyles Smith and Sean G. Pickner, DOGAMI, in 2011 (GIS file set, in press, 2012). Urban growth boundaries (2010) were provided by the Dregon Department of Land Conservation and Development (DLCD).

Transportation data (2010) provided by Curry County were edited by DOGAMI to improve the spatial accuracy of the features or to add newly constructed roads not present in the original data layer. Lidar data are from DOGAMI Lidar Data Quadrangles LDQ-2009-42124-H4-Langlois and LDQ-2009-42124-H5- Industries Special Paper 43, 57 p.

FlorasLake. Coordinate System: Oregon Statewide Lambert Conformal Conic, Unit: International Feet, Horizontal Datum: NAD 1983 HARN, Vertical Datum: NAVD 1988. Software: Esri ArcGIS® 10.0, Microsoft® Excel®, and Adobe<sup>®</sup> Illustrator<sup>®</sup>

Funding: This map was funded under award #NA09NW54670014 by the National Oceanic and Atmospheric Administration (NOAA) through the National Tsunami Hazard Mitigation Program. Map Data Creation/Development: Tsunami Inundation Scenarios. George R. Priest, Laura L. Stimely, Daniel E. Coe, Paul A. Ferro, Sean G. Pickner, Rachel R. Lyles Smith

Basemap Data: Kaleena L.B. Hughes, Sean G. Pickner Map Production: *Cartography:* Kaleena L.B. Hughes, Sean G. Pickner, Taylore E. Womble, Warren P. Roe Text: Don W.T. Lewis, Rachel R. Lyles Smith Editing. Don W.T. Lewis, Rachel R. Lyles Smith Publication. Deborah A. Schueller

Map Date. 09/13/2012

(NGDC/WDC) Global Historical Tsunami Database, Boulder, CO, USA. [http://www.ngdc.noaa.gov/hazard/tsu\_db.shtml]. Priest, G. R., 1995, Explanation of mapping methods and use of the tsunami hazard maps of the Oregon coast, Oregon Department of Geology and Mineral Industries Open-File Report 0-95-67, 95 p. nami Pilot Study Working Group (TPSW), 2006, Seaside, Oregon tsunami pilot study – modernization of FEMA flood hazard maps: U.S. Geological Survey Open-File Report 2006-1234, 90 p. + 7 app. [http://pubs.usgs.gov/of/2006/1234/].

References

Witter, R.C., Zhang, Y., Wang, K., Priest, G.R., Goldfinger, C., Stimely, L.L., English, J.T., and Ferro, P.A., 2011, Simulating tsunami inundation at Bandon, Coos County, Oregon, using hypothetical Cascadia and Alaska earthquake scenarios: Oregon Department of Geology and Mineral



telephone (971) 673-2331

http://www.naturenw.org

Scale 1:10,000